





s p e c i f i c a t i o n s

| | | | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|-------------------------------------------|
|  <p>26" TileVision®</p>  | External Dimensions (W x H x D) | 685 x 450 x 92 mm | |
| | Weight (Screen & Back Box) | 20Kg (44.09lb) | |
| | Power | AC/DC Adaptor | AC 100–240V, 50/60 Hz/24VDC/5.42A adaptor |
| | | Consumption | Max. 72W, Standby below 3W |
| | System | Analog | PAL-BG, I, DK/SECAM-BG, DK, L |
| | | Digital | DVB-T (MHEG-5) MPEG-2 decoding |
| | TV | Programme | VHF 2–13, UHF 21–69, Cable S1–S41 |
| | | | FVS 100 programme (Analog) |
| | LCD | Size | 26" (660 mm) Diagonal – Widescreen (16:9) |
| | | Resolution/Type | WXGA (1366 x 768) a-si TFT active matrix |
| | | Brightness | 450 cd/m2 |
| | | Contrast Ratio | 4,000:1 |
| | | Viewing Angle | 89°/89°/89°/89° (L/R/U/D) |
| | | Colour Depth | 8 bits (16.77 million colours) |
| Response Time | | 8 ms (Typ) | |
| Audio | Output | 3W + 3W RMS | |
| | System | Nicam, A2 Stereo | |
| Connections | EURO-SCART (Full), HDMI, S-Video, PC RGB, Component and Composite Video, Audio L/R, PC Audio In, Audio Out (Headphones), Speakers, Antenna/Tuner (Co-axial) | | |
| Control | RS-232 Port for Home Automation Systems, Infrared Link In & Out to interface with external equipment, RJ12 Port for Interactive Hotel TV System integration, Sky™ Remote Link to control a Sky™ box via the TileVision® | | |
| Features | Auto and Manual Programme, Aspect Ratio Control, Picture and Sound Memory, Teletext TOP/FLOP/MHEG-5 Teletext, Quick View, Real Time Clock | | |
| Accessories | Waterproof R/C with Holder, Standard R/C, Installation/Operating Instructions, Power Cord, DC Adaptor, Stereo Speaker & Cable, Back Box, Acrylic Bezel | | |

| | | | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|-------------------------------------------|
|  <p>19" TileVision®</p>  | External Dimensions (W x H x D) | 483 x 353 x 75 mm | |
| | Weight (Screen & Back Box) | 12Kg (26.5 lb) | |
| | Power | AC/DC Adaptor | AC 100–240V, 50/60 Hz/12VDC/6.67A adaptor |
| | | Consumption | Max. 50 W, Standby below 3 W |
| | System | Analog | PAL-BG, I, DK/SECAM-BG, DK, L |
| | | Digital | DVB-T (MHEG-5) MPEG-2 decoding |
| | TV | Programme | VHF 2–13, UHF 21–69, Cable S1–S41 |
| | | | FVS 100 programme (Analog) |
| | LCD | Size | 19" (480 mm) Diagonal – Widescreen (16:9) |
| | | Resolution/Type | WXGA (1440 x 900) a-si TFT active matrix |
| | | Brightness | 300 cd/m2 |
| | | Contrast Ratio | 1,000:1 |
| | | Viewing Angle | 85°/85°/80°/80° (L/R/U/D) |
| | | Colour Depth | 16.77 million colours (6 bit + Hi-FRC) |
| Response Time | | 5 ms | |
| Audio | Output | 3W + 3W RMS | |
| | System | Nicam, A2 Stereo | |
| Connections | EURO-SCART (Full), HDMI, S-Video, PC RGB, Component and Composite Video, Audio L/R, PC Audio In, Audio Out (Headphones), Speakers, Antenna/Tuner (Co-axial) | | |
| Control | RS-232 Port for Home Automation Systems, Infrared Link In & Out to interface with external equipment, RJ12 Port for Interactive Hotel TV System integration, Sky™ Remote Link to control a Sky™ box via the TileVision® | | |
| Features | Auto and Manual Programme, Aspect Ratio Control, Picture and Sound Memory, Teletext TOP/FLOP/MHEG-5 Teletext, Quick View, Real Time Clock | | |
| Accessories | Waterproof R/C with Holder, Standard R/C, Installation/Operating Instructions, Power Cord, DC Adaptor, Stereo Speaker & Cable, Back Box, Acrylic Bezel | | |

TILEVISION®

the bathroom television



19" and 26" waterproof LCD TVs

No new bathroom is complete without a **TILEVISION®**

A TileVision® is a completely independent digital television – totally waterproof (IP65) and totally tamperproof.

The heated 6 mm safety glass screen keeps the picture clear of condensation, making TileVision® perfect for use in high humidity areas such as bathrooms.

All functions, including setup and tuning are performed using the waterproof remote control.

As well as receiving all free-to-view digital TV and radio with digital text, a TileVision® is fully compatible with Sky™ Remote Link, Multi-room AV systems and Hotel television networks via RS-232 and RJ12 connectors.



Available in Black, Mirror or Silver finish, the 19" and 26" televisions feature:

- Widescreen (16:9) TFT LCD screens
- DVB-T digital tuner receives all free-to-view television and radio
- Digital text and Interactive services (MHEG-5) via the red button
- Perfect picture from high brightness, high contrast LCD screens
- Ultra wide viewing angles ensure high picture quality from any position
- Superb sound through water resistant, flush mount, single stereo speaker
- Analogue tuner with Teletext and Fast Text
- HDMI connector for High Definition (HD) input plus SCART, Component, Composite, PC RGB and S-Video
- Built in Sky™ Remote Control Link to control the satellite receiver via the coaxial aerial cable
- Infrared Link in and out to allow interface with external equipment (DVD, STB etc.)
- Waterproof remote control with self-adhesive holder